

Please note that these instructions are general information.
Different requirements may apply depending on the article and printing process.
 Please refer to the following pages if necessary.

Software	Please use suitable DTP software, e.g. Adobe Illustrator, Acrobat, InDesign, etc. Office programs such as Word or PowerPoint are not suitable for creating high-quality print data. Data from Canva software is also only partially suitable. The printing of Office or Canva data is usually only possible with restrictions, subsequent corrections and great effort (at EXTRA costs).	
Document Format	In a ratio of 1:1 for regular prints and 1:10 for oversized files (with any side over 200 inches).	
Cut	Bleed	0.125" outside the cut line (if required or unless otherwise noted on the following pages) Bleed must be created as such (in the bleed settings) in the document. An enlarged document format does not count as a bleed allowance.
	Contour Cut	Contour line should have a magenta CMYK stroke (C0/M100/Y0/K0) on a separate layer in the background.
	Digital Transfer and Foil Printing	A 0.25 pt overprinting contour in the special color "CutContour" (C0/M100/Y0/K0) should be placed in the foreground.
Document Contents	Font / Text	Convert to paths or embed in the PDF
	Images	Embed or send placed / linked images Image formats: eps, tif, jpg, png
	Optimum resolution: 72 - 300 dpi (depending on print size, article and application). Please do not create large-format print data with unnecessarily high resolution. This would only increase the processing time and the associated costs. Examples: · Design for a construction fence banner, which will be viewed from a distance or when driving past - a resolution of 72 dpi is sufficient here. · Design for a letterhead which is viewed at close range - a resolution of 300 dpi is recommended here. The resolution is, however, only a technical guideline. Depending on the motif and the quality of the image, a lower resolution may still be sufficient. Similarly, a higher resolution may not always be sufficient, for example, if an image has been interpolated (extrapolated). Please note that a scale other than 1:1 may require compression / recalculation! A resolution of 720 - 3,000 dpi is required at a scale of 1:10.	
File Format	We prefer printable PDF data in accordance with the PDF/X4 standard. Other possible file formats by arrangement: eps, ai, tif, jpg, png	
Colors	Please ensure that the overprint settings are correct. No liability is assumed for printing errors caused by incorrect overprinting settings. Digital Printing Please create data in CMYK, not RGB. Use the color profile US Web Coated SWOP v2. RGB data will automatically be converted to CMYK, which can lead to significant color shifts. Special colors can only be simulated in digital printing. A 100% match is not possible. An approximation is possible – however, it should be confirmed through a print proof that you provide to us. Please discuss further details with your sales representative. Deep Black Surfaces C50/M50/Y50/K100 White Underlay Create areas in overprinting white (C0/M0/Y0/K0) on a separate layer and place them in the foreground. Color Control On request, we will be happy to provide you with a proof as an additional color check.	
Service	Do you need a custom design for your print job? Then contact us! We will be happy to create your custom print design and file. (Costs according to time and effort)	
Delivery of Data	via Shop Upload	You can easily upload your print data after placing your order.
	via E-Mail	to your contact person (data volume of up to approx. 15 MB)
	via Download Link	Send us your data via download link



- ☐ Board size (ø 900)
- ☐ End size (ø 880)
- Position of screws (ø 13)
visible as a slight dent in the film
 - Position of pins (ø 6)

!

The print is on a white self-adhesive film measuring ø 880 mm, adhered to a panel of ø 900 mm.

The inner circle is cut. This contour later protrudes slightly, curving outwards. This circle rotates - texts and logos can therefore be upside down.

Please use the print template on the next page 1:1!

Include the Through Cut in the background on your print data. This must not be visible but can be coloured in white.

Measurements in mm

Print size	ø 880
Bleed	+2 mm bleed on all sides Please do not include any print markings (register marks, cut marks, etc.)
Colour	CMYK, colour profile for digital print: ISO Coated V2 (ECI) "Overprinting" not permitted - no liability will be accepted for print errors generated in this way.
Document content	Fonts vectorised, pictures embedded (Resolution 250 - 300 dpi)
File type	PDF file in PDF/X4-Standard



